SAFETY DATA SHEET

Issue Date: April 2020 Revision No: 1.0



1. IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

PX SUPER DOT 4 LV

Code : SDOT4LV
Use : Brake Fluid

Name: Phoenix Lubricants Pty Ltd (ABN 41 820 770 617)

Address: 2 Paul Court, Dandenong Vic 3175

Telephone : (03) 9791 7661 **Facsimile** : (03) 9791 8831

Email: info@phoenixlubricants.com.au **Web**: www.phoenixlubricants.com.au

2. HAZARD IDENTIFICATION

NOT A HAZARDOUS CHEMICAL ACCORDING TO CRITERIA OF SAFE WORK AUSTRALIA
NOT DANGEROUS GOODS FOR TRANSPORT ACCORDING TO AUSTRALIAN DANGEROUS GOODS CODE (ADGC)

Poisons Schedule : Not Scheduled

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS:

Component	CAS No.	% Proportion
2- (2- (2- Butoxyethoxy) ethoxy) ethano	143- 22- 6	<4 %
Ethanol, 2- (2- methoxyethoxy) -	111- 77- 3	<2 %
Diisopropanolamine	110- 97- 4	<2 %
Other ingredients classified as not hazardous according to Safe Work Australi	Balance	

4. FIRST AID MEASURES

REMOVE FROM EXPOSURE IF SAFE TO DO SO

Swallowed: • Wash mouth with water

Unlikely exposure route • Give a glass of water to drink

Do not induce vomiting

Seek immediate medical attention

Eye : • Remove contact lenses if present and easy to do so

• Hold eye open

• Wash gently for fifteen (15) minutes

• Seek medical attention

Skin: • Flush skin with water for fifteen (15) minutes or

Wash skin with soap and waterRemove contaminated clothing

• If symptoms develop seek medical attention

Inhalation of oil mist/spray

Unlikely exposure route

Remove from exposureLoosen/remove clothing

If breathing affected, clear airways

Print Date: 27/05/2020 Page 1 of 6 SDS- PX SUPER DOT 4 LV

- Give oxygen if qualified to do so
- Commence CPR if required and qualified to do so
- Seek immediate medical attention

ADVICE TO DOCTOR

- Treat symptomatically with supportive care.
- For further information contact:

AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26

NEW ZEALAND POISONS INFORMATION CENTRE 24 HOUR SERVICE 0800 764 766

5. FIREFIGHTING MEASURES

Suitable Extinguishing

Media

In case of fire, appropriate extinguishing

media includes:

• Dry Chemical Powder

SprayFoam

Do not use water jets. Use water spray to cool fire

exposed containers.

Hazards from Combustion :

Products

Under fire conditions this product may emit toxic

and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of

nitrogen.

Precautions for Fire : Fighters - Special Equipment Positive pressure self-contained breathing

apparatus (SCBA)

• Protective fire fighting clothing

• Fight from upwind

6. ACCIDENTAL RELEASE MEASURES

Spills or Leaks :

- Wear PPE as per this SDS
- · Remove ignition sources
- Absorb / contain waste, use earth, vermiculite, inert material
- Collect and seal in appropriate container
- Label the container
- Cover all drains
- Use spark proof tools
- Surfaces will be slippery
- · Create bund
- Observe regulatory reporting requirements (Incident Notification)

Disposal:

• Dispose of in accordance with State, Local Government, EPA or related Regulations or Codes of Practice.

7. HANDLING AND STORAGE

Precautions for Safe Handling

- Eye wash and safety shower to be available in the workplace.
- Wear PPE as per this SDS
- Compliant eyewash to be provided for external work.
- Observe good personal hygiene practices.
- · Wash hands thoroughly after handling.
- Avoid contact with skin and eyes.
- Limit the stock at work place (in accordance with AS1940: The storage and handling of flammable and combustible liquids)
- Use only in well ventilated areas. Ensure TLV's (threshold limit values) are not exceeded
- Wear respiratory protection if oil mists present.
- · Report incidents.
- No smoking, eating, drinking in the work area.
- Remove contaminated clothing before entering eating areas.

Conditions for Safe : Storage

- Store away from food, drink and animal feedstuffs.
- Store away from oxidising agents and strongly acid or alkaline materials.
- Provide ventilation.
- Separate or segregate from incompatibles (in accordance with regulatory requirements).
- · Avoid direct sunlight.
- Keep protected from weather.
- Provide spill kit.

Container Type :

• Store in original packaging as approved by manufacturer or regulatory direction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONSTITUENT DATA

Components	CAS-No.	Type	Value
Oil Mist		TWA	5mg/m ³

ENGINEERING CONTROLS

• Provide local exhaust ventilation when exposure standards might be exceeded.

PERSONAL PROTECTION

Eye Protection : Wear chemical splash goggles or face shield in accordance with AS/NZS1337, Eye

protection for industrial applications.

Gloves : Wear chemical protective gloves (eg nitrile) in accordance with AS/NZS 2161.1 -

Occupational protective gloves, selection, use and maintenance where contact

may occur.

Clothing : Wear body protective clothing and industrial footwear in accordance with AS2919 -

Industrial clothing.

Respiration: If oil mists are present when ventilation is inadequate, wear an approved respirator with

particulate filter in accordance with AS/NZS1715 - Selection, use and maintenance





















Available

Side shields

PVC

Industial

Non slip

Organic

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Light brown liquid

Odour : Mild pH : 7 – 8.5

Vapour Pressure : 1mbar (20°C), 1mbar (50°C)

Vapour Density : Not provided
Boiling Point : Not provided
Freezing / Melting Point : Not provided
Solubility in Water : Not soluble

Solubility in Solvents : Soluble in petroleum solvents

Specific Gravity or Density : 1.06

INFORMATION FOR FLAMMABLE MATERIALS

Flash Point : 135°C

Upper Explosive Limit : NOT PROVIDED Lower Explosive Limit : NOT PROVIDED Ignition Temperature : Not provided

ADDITIONAL INFORMATION

Specific Heat Value : Not provided
Particle Size : Not provided
VOC Content : Not provided
Evaporation Rate : Not provided
Octanol / Water Partition : Not provided

Coefficient

Saturation Vapour : Not provided

Concentration

Decomposition: Not provided

Temperature

Electrostatic Stability : Not provided

10. STABILITY AND REACTIVITY

Chemical Stability: Product is stable under normal conditions of use, storage and temperature.

Conditions to Avoid : Avoid excessive heat, static charges, sources of ignition.

Incompatible Materials : Incompatible with oxidising agents, strong acids and bases.

Hazardous Decomposition : Under fire conditions this product may emit toxic and/or irritating fumes, smoke and

Products gases including carbon monoxide, carbon dioxide and oxides of nitrogen

11. TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS (IMMEDIATE OR WITHIN 14 DAYS - SHORT TERM)

Swallowed (Oral): If ingested may cause gastric irritation.

Eye: Mild Eye irritant.

Skin (Dermal) : Mildly irritating to skin on prolonged exposure. Repeated or prolonged skin contact may

result in defatting, and dermatitis.

Inhalation: Strong concentrations of mist or spray may be irritating to the respiratory tract and for

mucous membranes with the risk of headaches, dizziness and nausea.

CHRONIC (MEDIUM OR LONG TERM)

Long term exposure may result in skin sensitisation in susceptible individuals.

MIXTURE VERSUS INGREDIENT

Print Date: 27/05/2020 Page 4 of 6 SDS- PX SUPER DOT 4 LV

Not provided

SUMMARY OF TOXICITY DATA

Component	CAS-No.	Data
Not available		

CARCINOGENICITY

• See Section 3

12. ECOLOGICAL INFORMATION

Ecotoxicity: Harmful to aquatic organisms, may cause long term adverse effects in the aquatic

environment.

Persistence / Degradability: Will persist. Not readily bio degradable.

Mobility: Floats on water - will be absorbed by earth.

Bio-accumulative Potential : May bio-accumulate

Environmental Fate

(Exposure)

Do not allow waste product to reach waterways, drains and sewers

Component	CAS-No.	Data
Not provided		

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Special Precautions for : Landfill or Incineration

Do not dispose to drains or waterways. See Section 6.

14. TRANSPORT INFORMATION

Special Precautions : Not regulated under Australian or International Dangerous Goods Codes, but Class

5 goods require segregation from combustible liquids in placard loads.

UN Number : Not allocated UN Proper Shipping Name : Not allocated

Dangerous Goods Class

and Subsidiary Risk

Not dangerous goods,

Packing Group : Not allocated Hazchem Code : Not allocated

15. REGULATORY INFORMATION (AUSTRALIA)

- Workplace Exposure Standards for Atmospheric Contaminants [Safe Work Australia, April 2013]
- Australian Code for Transport of Dangerous Goods by Road and Rail
- AS1940: The storage and handling of flammable and combustible liquids
- State Work Health and Safety/Occupational Health and Safety Regulations

16. OTHER INFORMATION

References: For detailed advice on personal protective equipment, refer to the following Australian

Standards:

HB9 (Handbook 9) Manual of industrial personal protection
AS/NZS 1337: Eye protectors for industrial applications

AS/NZS 1715: Selection, use and maintenance of respiratory devices

• AS/NZS 1716: Respiratory protective devices

CONTACT POINT

For information concerning details on this Safety Data Sheet, **Phoenix Lubricants Pty Ltd, 2 Paul Court, Dandenong Vic,** (03) 9791 7661

All reasonable care has been taken to ensure that the information and advice contained herein is accurate at the time of printing. However, Phoenix Lubricants Pty Ltd accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

Note:

This SDS is derived from International and Australian data and is formatted in accordance with the Safe Work Australia Code of Practice. Modifications are not made to technical data except where terminology is unclear or additional information is required to satisfy Australian requirements.

SOURCE FOR DATA

SDS Issue Date : April 2020

Revision No: : 1

Manufacturer / Supplier : Phoenix Lubricants Pty Ltd

 Print Date: 27/05/2020
 Page 6 of 6
 SDS- PX SUPER DOT 4 LV