SAFETY DATA SHEET

Issue Date: January 2017 Revision 3.0 Date: 05/08/2019



IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY 1.

PX COMPRESSOR OIL 68

Code COMP68 Use Compressor Oil

Phoenix Lubricants Pty Ltd (ABN 41 820 770 617) Name

Address 2 Paul Court, Dandenong Vic 3175

(03) 9791 7661 Telephone **Facsimile** (03) 9791 8831

> Email: info@phoenixlubricants.com.au Web: www.phoenixlubricants.com.au

2. HAZARD IDENTIFICATION

NOT A HAZARDOUS CHEMICAL ACCORDING TO CRITERIA OF SAFE WORK AUSTRALIA NOT DANGEROUS GOODS FOR TRANSPORT ACCORDING TO AUSTRALIAN DANGEROUS GOODS CODE (ADGC)

Poisons Schedule : Not Scheduled

3. **COMPOSITION / INFORMATION ON INGREDIENTS**

INGREDIENTS:

Component	CAS No.	% Proportion
Severely refined petroleum distillates	Not provided	Not provided
Other ingredients classified as not hazardous a	Balance	

The petroleum oils in this product contain less than 3% DMSO extract as measured by IP346 test method.

4. FIRST AID MEASURES

REMOVE FROM EXPOSURE IF SAFE TO DO SO

Swallowed: · Wash mouth with water

• Give a glass of water to drink Unlikely exposure route

Do not induce vomiting

Seek immediate medical attention

• Remove contact lenses if present and easy to do so Eye:

• Hold eye open

• Wash gently for fifteen (15) minutes

· Seek medical attention

Skin: • Flush skin with water for fifteen (15) minutes or

> • Wash skin with soap and water Remove contaminated clothing

· If symptoms develop seek medical attention

Inhalation of oil mist/spray :

Unlikely exposure route

 Remove from exposure · Loosen/remove clothing

• If breathing affected, clear airways

Give oxygen if qualified to do so

· Commence CPR if required and qualified to do so

· Seek immediate medical attention

Print Date: 14/08/2019 Page 1 of 6 SDS - PX Compressor Oil 68

ADVICE TO DOCTOR

- Treat symptomatically with supportive care.
- For further information contact:

AUSTRALIAN POISONS INFORMATION CENTRE 24 HOUR SERVICE 13 11 26

NEW ZEALAND POISONS INFORMATION CENTRE 24 HOUR SERVICE 0800 764 766

5. FIREFIGHTING MEASURES

Hazchem Code : 3Y

Fire & Explosive Properties : C2 Combustible liquid - Flashpoint 205°C

Suitable Extinguishing Media

In case of fire, appropriate extinguishing

media includes:

• Dry Chemical Powder

CO₂
 Foam

Do not use water jets. Use water spray to cool fire

exposed containers.

Hazards from Combustion :

Products

Product is a mobile liquid. Vapours may travel and accumulate in low lying areas and can build explosive mixtures with air. Incompatible with strong oxidising agents, acids/alkalis. Combustion may produce oxides of carbon, nitrogen and sulphur, dense black smoke, toxic decomposition gases, and airborne unidentified organic and inorganic solid and liquid particulates.

Precautions for Fire : Fighters - Special Equipment

- Positive pressure self-contained breathing apparatus (SCBA)
- Protective fire fighting clothing
- Fight from upwind

HAZCHEM Emergency **Action Code** OR FIRE OR SPILLAG COARSE SPRAY FINE SPRAY FOAM NORMAL PROTEIN DRY AGENT ALCOHOL RESISTANT LTS R DILUTE s BA & FIRE KIT T W LTS X CONTAIN Υ BA & FIRE KIT Z PUBLIC SAFETY HAZARD

LEGEND DRY AGENT Do not use water ALCOHOL RESISTANT FOAM *2 OR *3 When *appears in front of 2 or 3 in Hazchem code use alcohol resistant foam if available V Substances can be violently or even explosively reactive, including combustion LTS Liquid-Tight Chemical Protective Suit with BA. Full FIRE KIT to also be worn for protection when: Liquid-Oxygen Liquid-Oxygen Liquid-Oxygen Class or sub-nsk 3 Division 5.1 PGI with sub-nsk 6.1 or 5 transported at temperature >100°C are involved DILUTE May be washed to drains with large quantities of water. CONTAIN Prevent, by any means available, spillage from entering drains or water courses E People to be warned to stay indoors with all doors and windows closed. Evacuation may need to be considered Joint Incident Control decision

6. ACCIDENTAL RELEASE MEASURES

Spills or Leaks :

- Wear PPE as per this SDS
- Remove ignition sources
- Absorb / contain waste, use earth, vermiculite, inert material
- Collect and seal in appropriate container
- Label the container
- · Cover all drains
- · Use spark proof tools
- · Surfaces will be slippery
- · Create bund
- Observe regulatory reporting requirements (Incident Notification)

Disposal:

• Dispose of in accordance with State, Local Government, EPA or related Regulations or Codes of Practice.

7. HANDLING AND STORAGE

Precautions for Safe : Handling

- Eye wash and safety shower to be available in the workplace.
- Wear PPE as per this SDS
- Compliant eyewash to be provided for external work.
- Observe good personal hygiene practices.
- · Wash hands thoroughly after handling.
- Avoid contact with skin and eyes.

- Limit the stock at work place (in accordance with AS1940: The storage and handling of flammable and combustible liquids)
- Use only in well ventilated areas. Ensure TLV's (threshold limit values) are not exceeded.
- Wear respiratory protection if oil mists present.
- Report incidents.
- No smoking, eating, drinking in the work area.
- Remove contaminated clothing before entering eating areas.

Conditions for Safe Storage

- Store away from food, drink and animal feedstuffs.
- Store away from oxidising agents and strongly acid or alkaline materials.
- · Provide ventilation.
- Separate or segregate from incompatibles (in accordance with regulatory requirements).
- Avoid direct sunlight.
- Keep protected from weather.
- Provide spill kit.

Container Type : • Store in original packaging as approved by manufacturer or regulatory direction.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONSTITUENT DATA

Components	CAS-No.	Туре	Value
Oil Mist		TWA	5mg/m ³

ENGINEERING CONTROLS

• Provide local exhaust ventilation when exposure standards might be exceeded.

PERSONAL PROTECTION

Eye Protection: Wear chemical splash goggles or face shield in accordance with AS/NZS1337, Eye

protection for industrial applications.

Gloves : Wear chemical protective gloves (eg nitrile) in accordance with AS/NZS 2161.1 -

Occupational protective gloves, selection, use and maintenance where contact may

occur.

Clothing: Wear body protective clothing and industrial footwear in accordance with AS2919 -

Industrial clothing.

Respiration: If oil mists are present when ventilation is inadequate, wear an approved respirator with

particulate filter in accordance with AS/NZS1715 - Selection, use and maintenance of

respiratory protective devices







or T







Non slip





Available

Side shields

PVC

Industial

Organic

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear Amber/brown liquid

Odour : Mild

pH : Not providedVapour Pressure (kpa) : Not providedVapour Density : Not provided

Boiling Point : Not provided
Freezing / Melting Point : Not provided
Solubility in Water : Not soluble

Solubility in Solvents : Soluble in petroleum solvents

Specific Gravity or Density : 0.879

Print Date: 14/08/2019 Page 3 of 6 SDS – PX Compressor Oil 68

INFORMATION FOR FLAMMABLE MATERIALS

205°C Flash Point :

Upper Explosive Limit: **NOT PROVIDED Lower Explosive Limit** NOT PROVIDED **Ignition Temperature** Not provided

ADDITIONAL INFORMATION

Specific Heat Value Not provided **Particle Size** Not provided VOC Content : Not provided **Evaporation Rate** Not provided Kinematic Viscosity @ 40°C 68 cSt Kinematic Viscosity@ 100°C 8.7 cSt Octanol / Water Partition Not provided

Coefficient

Saturation Vapour : Not provided

Concentration

Decomposition Not provided

Temperature

Electrostatic Stability Not provided

Pour Point -18 °C

10. STABILITY AND REACTIVITY

Chemical Stability Product is stable under normal conditions of use, storage and temperature.

Conditions to Avoid Avoid excessive heat, static charges, sources of ignition.

Incompatible Materials Incompatible with oxidising agents, strong acids and bases.

Hazardous Decomposition Oxides of carbon, nitrogen and sulphur, dense black smoke, toxic decomposition gases,

Products

and airborne unidentified organic and inorganic solid and liquid particulates - see

Section 5.

Hazardous Reactions When heated above 200°C, vapours may form flammable mixture with air

11. TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS (IMMEDIATE OR WITHIN 14 DAYS - SHORT TERM)

Swallowed (Oral) If ingested may cause gastric irritation.

> Eye Mild Eye irritant.

Skin (Dermal) Irritating to skin on prolonged exposure. Repeated or prolonged skin contact may result

in defatting, and dermatitis.

Inhalation Strong concentrations of vapour, mist or spray may be irritating to the respiratory tract

and for mucous membranes with the risk of headaches, dizziness and nausea.

CHRONIC (MEDIUM OR LONG TERM)

• Long term exposure will result in skin sensitisation in susceptible individuals.

MIXTURE VERSUS INGREDIENT

Not provided

SUMMARY OF TOXICITY DATA

Component	CAS-No.	Data
Not provided		

CARCINOGENICITY • See Section 3 COMPOUNDING EFFECTS • Not provided

USED OILS AND GREASES

- Products resulting from the operation of the vehicle/ machinery may contain contaminants. Used oil and grease may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used oil and grease must therefore be avoided and a high standard of personal hygiene maintained.
- Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
- At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of low volatility. May be harmful by inhalation if exposure to mists or fumes resulting from thermal decomposition products occur.

12. ECOLOGICAL INFORMATION

Ecotoxicity: Harmful to aquatic organisms, may cause long term adverse effects in the aquatic

environment.

Persistence / Degradability: Will persist. Not readily bio degradable.

Mobility: Floats on water - will be absorbed by earth.

Bio-accumulative Potential: May bio-accumulate

Environmental Fate

FOR OILS AND GREASES

(Exposure)

Do not allow waste product to reach waterways, drains and sewers

Component	CAS-No.	Data
Not provided		

13. DISPOSAL CONSIDERATIONS

Disposal Methods

Special Precautions for Landfill or Incineration

Do not dispose to drains or waterways. See Section 6.

14. TRANSPORT INFORMATION

Special Precautions : Not regulated under Australian or International Dangerous Goods Codes, but Class 5

goods require segregation from combustible liquids in placard loads.

UN Number : Not allocated UN Proper Shipping Name : Not allocated

Dangerous Goods Class

and Subsidiary Risk : Class C2 Combustible Liquid

Packing Group : Not allocated

Hazchem Code : 3Y

15. REGULATORY INFORMATION (AUSTRALIA)

- National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003]
- Australian Dangerous Goods Code for Transport of Dangerous Goods by Road and Rail
- Standard Uniform Scheduling of Drugs and Poisons
- States Hazardous Substances Regulations

Print Date: 14/08/2019 Page 5 of 6 SDS – PX Compressor Oil 68

16. OTHER INFORMATION

References: For detailed advice on personal protective equipment, refer to the following Australian

Standards:

HB9 (Handbook 9) Manual of industrial personal protection
AS/NZS 1337: Eye protectors for industrial applications

• AS/NZS 1715: Selection, use and maintenance of respiratory devices

• AS/NZS 1716: Respiratory protective devices

CONTACT POINT

For information concerning details on this Safety Data Sheet, **Phoenix Lubricants Pty Ltd, 2 Paul Court, Dandenong Vic,** (03) 9791 7661

All reasonable care has been taken to ensure that the information and advice contained herein is accurate at the time of printing. However, Phoenix Lubricants Pty Ltd accepts no tortious or contractual liability for any loss or damages suffered as a consequence of reliance on the information and advice contained herein.

Note:

This SDS is derived from International and Australian data and is formatted in accordance with the Safe Work Australia Code of Practice. Modifications are not made to technical data except where terminology is unclear or additional information is required to satisfy Australian requirements.

SOURCE FOR DATA

MSDS Issue Date : 02/03/2013

MSDS Revision 3.0 Date : 05/08/2019

Manufacturer / Supplier : Phoenix Lubricants Pty Ltd

 Print Date: 14/08/2019
 Page 6 of 6
 SDS – PX Compressor Oil 68