# **Technical Data**

## **TOTAL SERVICE SERIES PX** HIGH PERFORMANCE 25W-70

## **Product Description**

PX High Performance 25W-70 is a technically advanced high viscosity oil made from a unique blend of additives to produce exceptional viscosity stability and will not thin out or shear even under the most severe conditions.

## **Applications/ Benefits**

PX High Performance 25W-70 meets or exceeds the requirements of an SG/ CD engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion. PX High Performance 25W-70 is a must for all turbo charged passenger vehicles both diesel and petrol, and is highly desirable for the following applications:

- High performance local and imported cars.
- Racing engines.
- Engines running flat tappet cams.
- Off road recreational vehicles.
- Wet Clutch applications and where oil is subject to very high temps.
- Vehicles using both leaded and unleaded fuel.

### **Typical Characteristics**

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	25W-70
Specific Gravity @ 15 0 C	ASTM D-4052	0.889
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	260.4
@ 100 0 C (cSt)	ASTM D-445	28.91
Viscosity Index	ASTM D-2270	145

### **Specifications**

API: SG/CD

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS 2 Paul Court Dandenong Victoria 3175 Tel. +61 3 9791 7661

www.phoenixlubricants.com.au Email: info@phoenixlubricants.com.au