

# Technical Data

## TOTAL SERVICE SERIES

### PX TAC-PLUS CHAIN & BAR 150

#### Product Description

PX TAC-PLUS CHAIN & BAR 150 oil protects saw teeth and chains from abrasive wear and can be applied manually or in automatic lubrication systems.

PX TAC-PLUS CHAIN & BAR 150 oil is a tacky extreme pressure and anti-corrosion lubricant with excellent cling characteristics that resists throw off, water wash off and corrosion from tree sap. PX TAC-PLUS CHAIN & BAR 150 oil will adhere to the working surface of cutting bars, chains, scissor snickers under high speed assisting in increasing equipment life

#### Applications/ Benefits

- Excellent cling characteristics
- Resists throw off
- Resists corrosion from tree sap

#### Typical Characteristics

Test Description	Method	Result
ISO Grade		150
Specific Gravity @ 15 0 C	ASTM D-1298	0.868
Flash Point, 0 C	ASTM D-92	216
Pour Point, 0 C	ASTM D-5950	-14
@ 40C (cSt)	ASTM D-445	150 Typical
@ 100 0 C (cSt)	ASTM D-445	13.9

#### Specifications

ISO 150

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)