

# Technical Data

## TECHNICIAN SERIES

## PX TOTAL DRIVELINE 75W-85

### Product Description

PX TOTAL DRIVELINE 75W-85 is a fully synthetic PAO high tech gear oil formulated with advanced additive technology providing the best available protection for modern gearboxes, transfer/ drive cases and axles, especially in arduous conditions or where extended drain intervals are required.

### Applications/ Benefits

The additive used in PX TOTAL DRIVELINE 75W-85 has over 28 million kilometres of field testing in passenger car and commercial vehicles and is an OEM endorsed additive technology. The advantage of using this technology is that it is a total driveline lubricant which can be used in synchromesh transmissions, transfer cases & differentials where GL-4 and or GL-5 are required.

- Provides extended oil drain intervals
- Reduces operating temperatures
- Extremely thermal stability with exceptional cleanliness
- Reduces product inventory
- Avoids miss-applications
- OEM endorsed additive technology
- Suits automotive synchromesh transmissions, transfer cases & differentials

### Typical Characteristics

SAE Viscosity Grade	75W-85
Specific Gravity @ 15 deg. C	0.862
Flash Point	202
@ 40C (cSt)	88
@ 100 0 C (cSt)	13.3
Viscosity Index	152
Brookfield @ -40°C (m.Pa.s.)	48000
Pour Point, Deg. C	-48

### Specifications

- API: GL4, GL5, MT-1
- MB: 235.4
- SAE: 75W-85, J2360

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)