

Technical Data

TECHNICIAN SERIES

PX XTREME C3 5W-30

Product Description

PX Xtreme C3 is a fully synthetic engine oil that has been processed using the latest patented technology. Reinforced with a powerful additive package, PX Xtreme C3 is ideal for modern high output, low emission, super or turbo charged, DOHC or GDI engines that are commonly found in latest European and Japanese models.

With a naturally high viscosity index and low volatility, PX Xtreme C3 offers high performance, uncompromised protection to petrol or diesel engines. Due to its excellent anti oxidation property, PX Xtreme C3 exhibits extended drain intervals and potential fuel saving.

PX Xtreme C3 meets stringent API & ACEA standards for petrol and diesel engines and is suitable for use in the widest range of modern passenger cars and light commercial vehicles.

Applications/ Benefits

- Improves engine performance.
- Superior high temperature protection.
- High zinc anti-wear formulation for superior engine protection
- Excellent protection for Diesel Particulate Filters (DPF).

Typical Characteristics

Test Description	Result
SAE Viscosity Grade	5W-30
Specific Gravity @ 15 deg. C	0.850
Kinematics Viscosity	
@ 40C (cSt)	71
@ 100 (cSt)	11.80
Viscosity Index	162
TBN	8.1



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au

Specifications

- API: SN/CF
- ACEA: C2, C3
- BMW: Longlife 04
- GM: Proprietary Fill – Diesel
- Fiat: 9.55535-S1
- Fiat: 9.55535-S3
- Mercedes Benz: 229.31/ 229.51/ 229.52
- PSA: B71 2290
- Renault: RN 0700/ 0710

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au

7 June 2019