

Technical Data

TOTAL SERVICE SERIES

PX AGRILUBE STOU 15W-40

Product Description

PX Agrilube is specially designed to meet the necessary lubrication requirements found in most compartments of a modern tractor. It incorporates the latest STOU and UTTO technology, and can eliminate the chance of using the wrong oil.

Applications/ Benefits

PX Agrilube being truly "Universal" oil, that is suitable for engines, transmissions, hydraulic systems, final drives, wet brakes, power take offs, hydrostatic and power steering systems in farm tractors and other implements. PX Agrilube is also suitable for all petrol and diesel engines where API CG4/ SF are specified.

Typical Characteristics

SAE Viscosity Grade	15W-40
Specific Gravity @ 15 Deg. C.	0.890
Flash Point	210 Deg. C.
Kinematics Viscosity	
@ 40C (cSt)	103.7
@ 100 0 C (cSt)	14.32
Viscosity Index	141
TBN (mgKOH/g)	10.9

Specifications

- API: CG4/SF & GL4
- ACEA: E3
- SAE: 15W-40
- ALLISON: C4
- CAT: TO-2
- CASE: MS 1204, MS 1206, MS 1207, MS 1209
- CASE NEW HOLLAND: MAT 3525/ 3526
- DAIMLER BENZ: 228.3
- FORD/ NEW HOLLAND: M2C-86B/ C, M2C-159B/ C, M2C-134D
- JOHN DEERE: J20C/ D, J27
- MASSEY FERGUSON: MF 1135, MF1139, MF1143, MF1144, MF 1145
- SPERRY VICKERS/ EATON: I-280-S, M-2950-S
- SAUER SUNSTRAND/ DANFOSS
- ZF TE-ML 06A, 06B (inc. 06R), 06C, 07B

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au