

Technical Data

TOTAL SERVICE SERIES

PX EXTREME POWER DIESEL CJ-4 15W-40

Product Description

PX Extreme Power Diesel CJ-4 is a premium universal lubricant required for diesel engines equipped with after treatment devices such as diesel oxidation catalysts and particulate filters. Blended from hydrocracked base stocks and a state of the art additive package, PX Extreme Power Diesel CJ-4 meets the latest API, ACEA and Top Tier European engine standards.

Applications/ Benefits

- Minimizes oil consumption, long drain intervals
- Provide unsurpassed control of soot
- Protection of highly stressed piston rings and cylinder liners
- Exceptional protection of valve train systems used in modern diesels
- Satisfying most diesel engine OEM oil demands
- Suitable for diesel engines meeting EURO 4 or EURO 5 emission requirements

Typical Characteristics

SAE Viscosity Grade	15W-40
Specific Gravity @ 15 0 C	0.8686
Flash Point, 0 deg. C	217
Pour Point, 0 deg. C	-36
Kinematics Viscosity	
@ 40C (cSt)	115.9
@ 100 0 C (cSt)	16.00
Viscosity Index	147
TBN (mgKOH/g)	10.12

Specifications

- API: CJ-4/SM
- Cummins: CES 20071/ 20081
- Deutz: DQC III-10 LA
- Global: DHD-1
- JASO: DH-2, DH-1
- MAN: M3275/ 3277
- Mercedes Benz: 228.31
- ACEA: E7, E9
- Mack: EO-O Premium Plus
- Caterpillar: ECF -1A, ECF -2, ECF-3
- Detroit Diesel: DDC 93K218/ 215
- MTU: 2.1
- Renault : RLD-3
- Volvo: VDS-4 , VDS-3

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au