

Technical Data

TOTAL SERVICE SERIES

PX HIGH PERFORMANCE 25W-60

Product Description

PX High Performance 25W-60 is a technically advanced high viscosity oil made from a unique blend of additives to produce exceptional viscosity stability, and will not thin out or shear even under the most severe conditions.

Applications/ Benefits

PX High Performance 25W-60 meets or exceeds the requirements of an SG/ CD engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion. PX High Performance 25W-60 is a must for all turbo charged passenger vehicles both diesel and petrol, and is highly desirable for the following applications:

- High performance local and imported cars.
- Engines running flat tappet cams.
- Racing engines.
- Off road recreational vehicles.
- 4-Stroke motor cycles including Harley Davidson.
- Wet Clutch applications and where oil is subject to very high temps
- Vehicles using both leaded and unleaded fuel.

Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	25W-60
Specific Gravity @ 15 0 C	ASTM D-4052	0.882
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	245.3
@ 100 0 C (cSt)	ASTM D-445	25.92
Viscosity Index	ASTM D-2270	139

Specifications

- API: SG/CD
- CCMC G4, D4, PD-2
- MIL-L-46152D,

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au