

# Technical Data

## TOTAL SERVICE SERIES

### PX MONO 30

#### Product Description

PX Mono 30 has been formulated to lubricate turbo-charged and normally aspirated diesel's operating under severe stress conditions in both on and off highway situations.

#### Applications/ Benefits

With its low phosphorous level and low sulphated ash content ensures its use for mixed fleet operators including those with petrol engines with catalytic converters. PX Mono 30 meets or exceeds the requirements of CF/ SF engine oil. It provides a high level of protection against wear, sludge formation and acid corrosion. PX Mono 30 assists in maintaining engine cleanliness and extending the life of all moving parts subject to wear.

- Helps extend engine life.
- Minimizes piston and combustion chamber deposits.
- Contains anti-corrosion agents.
- Recommended for petrol or diesel engines.

#### Typical Characteristics

Test Description	Method	Result
SAE Viscosity Grade	SAE J300	30
Specific Gravity @ 15 0 C	ASTM D-4052	0.880
Kinematics Viscosity		
@ 40C (cSt)	ASTM D-445	88
@ 100 0 C (cSt)	ASTM D-445	10.8
Viscosity Index	ASTM D-2270	110

#### Specifications

- API: CF/ SF
- MACK: EO-K, EO-K2
- MAN: M270
- MB: 228.0
- ALLISON: C4
- CAT: TO-2

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



**PHOENIX**®

PHOENIX LUBRICANTS  
2 Paul Court Dandenong Victoria 3175  
Tel. +61 3 9791 7661

[www.phoenixlubricants.com.au](http://www.phoenixlubricants.com.au)  
Email: [info@phoenixlubricants.com.au](mailto:info@phoenixlubricants.com.au)