Technical Data

TECHNICIAN SERIES PX TRANSMATIC CVT

Product Description

PX Transmatic CVT is blended from high-performance synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

PX Transmatic CVT has been specially designed for use in latest generations of Continuously Variable Transmissions (CVT) which transfers traction via steel-made traction chains or belts. It provides outstanding power transfer and better fuel-economy performance for CVTs as compared with the regular automatic transmissions.

Applications/ Benefits

PX Transmatic CVT meets or exceeds the performance requirements of OEM's that offer CVT's in their vehicles, including Audi, VW, Chrysler, BMW, Nissan and Subaru.

Typical Characteristics

Test Description	Result
Specific Gravity @ 15 0 C	0.8534
Flash Point, Deg. C	190
Pour Point, Deg. C	-45
Kinematics Viscosity	
@ 40C (cSt)	33.78
@ 100 0 C (cSt)	7.33

Specifications

- Audi/VW (TL 52180; G 052 180 A2)
- Toyota (TC)
- Nissan (NS-2)
- Mazda (CVT 3320)
- Mitsubishi (CVTF-J1)
- Subaru (NS-2 / Lineartronic CVTF, K0425Y0710)
- Mini Cooper (EZL 799)
- Hvundai/ Kia Genuine CVTF 1
- Suzuki (CVT 3320, TC / NS-2 /CVT Green 1)
- Dodge / Jeep (NS-2 / CVTF+4)
- GM/Saturn (DEX-CVT)

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS 2 Paul Court Dandenong Victoria 3175 Tel. +61 3 9791 7661

www.phoenixlubricants.com.au Email: info@phoenixlubricants.com.au