

Technical Data

TOTAL SERVICE SERIES

PX ULTRA-BLEND 15W-50

Product Description

PX Ultra-Blend 15W-50 is a true multifunctional petrol/diesel oil representing a new generation in motor oil that provides better protection from piston deposits, minimises oil thickening, sludge deposits, and provides exceptional anti-wear protection compared to oils with a lower API classification.

Applications/ Benefits

- Suitable for all late model petrol engine vehicles where using a 20W-50 engine oil is specified/ required.
- This product is also ideal for use in L.P.G fuelled vehicles and diesel engines where API CF performance is stipulated.
- Provides a high level of protection against wear, sludge formation and acid corrosion.

Typical Characteristics

Test Description	Result
SAE Viscosity Grade	15W-50
Specific Gravity @ 15 0 C	0.8732
Kinematics Viscosity	
@ 40C (cSt)	149.2
@ 100 0 C (cSt)	19.62
Viscosity Index	151
TBN (mgKOH/g)	7.6

Specifications

- API: SM/CF

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.



PHOENIX LUBRICANTS
2 Paul Court Dandenong Victoria 3175
Tel. +61 3 9791 7661

www.phoenixlubricants.com.au
Email: info@phoenixlubricants.com.au